CUT2



- •For 2 pipes with valve control, 2 and
- 4 pipes without valve control
- •Panel with three fan speed selection
- •Fan Coil ON / OFF
- •Summer / Winter selection
- Room thermostat

For Installation on Fan Coil Types KDT, KYT, KTP and KTT

CUT4



- •For 4 pipes with valve control
- Panel with three fan speed selection
- •Fan Coil ON / OFF
- •Summer / Winter selection
- Room thermostat

For Installation on Fan Coil Types KDT, KYT, KTP and KTT

RDF 510 - 530



- •3-speed fan control
- •Fan coil On/Off
- Heating or Cooling mode
- •Summer/ Winter operation selector
- Timer specification
- Automatic backlighting

RDF 800



- •3-speed fan control
- Touch screen
- •Heating and cooling mode at the same time
- •BMS (Building Management System)
- •Fan coil On/Off
- •Summer/ Winter operation selector
- Operation timer
- Automatic backlighting

SM-2008 FFS-L



- •3-speed fan control
- •Fan coil On/Off
- Heating or Cooling Mode
- •Summer/ Winter operation selector
- Operation timer
- Fan speed control
- Automatic backlighting

Room thermostat (UOT)



- 3-speed fan control
- Fan coil On/Off
- Heating or Cooling mode
- Summer/ Winter operation selector
- Valve control for 2 pipes
- Valve control for 4 pipes (RAB31)

VM: 2 & 3-way valve options





2 and 3- way valves are used for the purpose of thermostatic fluid control for the coils and are supplied loose or factory fitted. 3-way valves are available with 4-port option for the installation convenience.

APK: Rear cover



Used for covering the back of units in KDT and KYT types.

ALK: Lower cover



Used for covering the bottom of unit in KTP types.

AYK: Foot



Used for installing the unit to the floor in KDT types.

3VM3SG: 3-way valve installation kit



Used for 2-Pipe systems for GTT - GDT - GTA types.*

4VM3SG: 3-way valve installation kit



Used for 4-Pipe systems for GTT - GTA types. *

4VM3SK: 3-way valve installation kit



Used for 4-Pipe systems for GDT types. *

^{*} Supplied loose